



## 9 L. Foam FIRE EXTINGUISHER



CLIP DETAIL



FROST RESISTANCE  
(UP TO -30°C)

- **CYLINDER**  
Alloy steel, 3 pieces drawing, with clip, epoxy polyester powder painting, Red Ral 3000.
- **EXTINGUISHING AGENT**  
Water foam.
- **PROPELLANT**  
Dehumidified air or N<sub>2</sub>.
- **VALVE**  
M. 30x1.5, brass body, levers with red painting Ral 3000.
- **USE**  
A B fire rating  
(solid materials, flammable liquids).

*Note: image is for illustrative purpose only, the product purchased can has some differences*

9 L. foam fire extinguisher, temperature range from -30°C to +60°C, manufactured in accordance to **UNI EN 3-7**, certified according to the directive for pressure equipment PED 2014/68/EU.

Quality Product certification guaranteed by Bureau Veritas Italia.

Suitable for use on fire involving electrical voltages up to 1'000 V, at a distance of 1 mt.

APPROVED/CERTIFIED FIRE EXTINGUISHER:



FIRE  
RATING :



21

183


# 9 L. Foam FIRE EXTINGUISHER

## TECHNICAL SPECIFICATIONS


FIRE RATING	21 A 183 B
EXTINGUISHING AGENT	EW-30 foam (100 % Premix MG6 -30)
PROPELLANT	Dehumidified air or N <sub>2</sub> ,15 Bar at 20°C
TEMPERATURE RANGE	-30°C / +60°C
NOMINAL CHARGE	9 L.
FULL WEIGHT	~ 15,1 Kg
DIMENSIONS	Height(base-valve) 635 mm Diameter 170 mm
DISCHARGE TIME	34,5 sec.
VALVE TIGHTENING TORQUE	Minimum 45 Nm, Maximum 68 Nm
CYLINDER PRESSURE TEST	PT 27 bar
CYLINDER VOLUME	10,7 L.
SAFETY VALVE	Set between 20 and 26 bar
CYLINDER MATERIAL	Alloy steel
EXTERNAL/INTERNAL TREATMENT	Sandblast and epoxypolyestere powder painting, Red Ral 3000 colour/ Internal plastic lining

## PACKAGING

STANDARD : maximum 40 pieces for pallet  
(40 pieces for box, max 1 box for pallet)  
Pallet dimensions 100x120x80(h) cm




SINGLE PACKAGING  
ON REQUEST:  
- maximum 40 pieces  
on pallet 100x120



*Note: the packaging quantities and measurements are indicative and can be subject at changes*

## MAINTENANCE AND INSTALLATION

For outdoor or marine installation is recommended to protect the fire extinguisher with cover or box. Maintenance according to the rules in use in utilization country.



## SPARE PARTS

NUMBER	DESCRIPTION	
1	Valve M. 30x1.5	
2	Cylinder	
3	PVC dip tube	
4	Label	
5	Hose with dispensing nozzle	
6	Safety pin	
	Safety valve	
	Safety pin seal	
	EW-30 foam (9 L. recharge, ready to use)	
OPTIONAL	Wall-mounted bracket for cylinder with clip, red painting	